LEGEND

SITE FURNITURE/ACCESSORIES

KEY	MANUFACTURER	MAKE/MODEL	DESCRIPTION
▤	MIRACLE	1120 (5'6"x0'0")	STEEL PICNIC TABLE
▭	MIRACLE	1270 (6'0")	STEEL SLAT BENCH - PERMANENT
▪	IRON MTN. FORGE	210 x	2 LEVEL GROUP GRILL BARBEQUE
○	IRON MTN. FORGE	292-X2R	20 GA. LITTER RECEPTACLE - STATIONARY
⊕	HAWS	3176	HANDICAP DRINKING FOUNTAIN - EX. AGG.
A	MIRACLE	166-91CP	'STEELVILLE' CHILDREN'S PLAY STRUCTURE
⊛	MIRACLE	902	10'0" DIAMETER WHIRL
B	MIRACLE	166-92CP	'STEELVILLE' TOT LOT PLAY STRUCTURE
⊙	MIRACLE	918	SQUIRREL RIDER WITH 'C' SPRING
◉	MIRACLE	902	FROG RIDER WITH 'C' SPRING

SITE FEATURES

KEY	SIZE/TYPE	DESCRIPTION
▬▬	6"± DOUG. FIR	BOLLARDS - PRESSURE TREATED (SEE SHT. 26)
◉	4" O.D. GALV. STEEL	REMOVEABLE BOLLARDS - FLAT BLACK (SEE SHT. 26)
▬▬	6" CONCRETE	RETAINING WALL (SEE DETAIL SHEET 26)
⬭	———	PROPOSED CONTOURS (1'0" INTERVALS)
⊠	PACIFIC BELL	TRANSFORMER ON CONCRETE SLAB
▬▬	2"x6" REDWOOD	HEADER/BOARDS (SEE DETAIL SHEET 27)
▨	———	GROUNDCOVER AREA (SEE SHEET 25)
⁘	———	HYDROSEEDED LAWN AREA (SEE SHEET 25)
⁘	PDATCO #4	SAND PLAY AREA (SEE DETAIL SHEET 26)
▬▬	CONCRETE	(5' AND 10' WIDE AS SHOWN) PER CITY STANDARDS

NOTES

1. ALL BENCHES, PICNIC TABLES AND BARBEQUES TO HAVE CONCRETE PADS PER PAVING DETAIL SHEET 27 AND SPECIFICATIONS.
2. TRASH RECEPTACLES AND BENCHES TO HAVE BOLTS EMBEDDED IN 12" DIAMETER x 18"-24" CONCRETE FOOTINGS, 2" BELOW GRADE.
3. ALL PICNIC TABLES TO BE BOLTED DOWN WITH 2" x 6"± x 11/16" GALVANIZED STEEL 'U' BRACKETS BOLTED INTO THE CONCRETE PAD. PROVIDE 4 BRACKETS PER TABLE, 'U' IN BRACKET TO FIT SNUGLY OVER 1 5/8" O.D. PIPE LEGS. ANCHOR BOLTS 5/8" x 6" MAY BE EMBEDDED IN CONCRETE SLAB W/ WASHER AND NUT 1" MAXIMUM ABOVE GRADE.
4. REMOVEABLE AND STATIONARY BOLLARDS TO BE PLACED 24" FROM FACE OF CURB. STATIONARY BOLLARDS TO BE SPACED @ 5'0" O.C. REMOVEABLE BOLLARDS TO BE SPACED @ 4'0" O.C.
5. FIELDSTONE BOULDERS TO BE BURIED 1/3 BELOW GRADE. PLACEMENT OF INDIVIDUAL BOULDERS IN OUTCROPS MAY REQUIRE SUPERVISION BY LANDSCAPE ARCHITECT.
6. ALL PATHS TO HAVE REDWOOD BENDERBOARDS OR HEADERS PER DETAIL SHEET 27. SUBGRADE TO BE COMPACTED 95%. PROVIDE 2" CLEAN SAND COMPACTED 95% AS BASE, AND CONCRETE 4" THICK AND LAID PER CITY OF SANTA ROSA REQUIREMENTS.
7. MIRACLE PARK AND PLAY EQUIPMENT AVAILABLE THRU DALE GREEN ASSOCIATES, ALAMO, CA. (415) 837-0755.
8. SEE DETAIL SHEETS 26 AND 27, AND SPECIFICATIONS FOR ADDITIONAL NOTES.
9. SEE SHEET 22 FOR PATH AND CURB LAYOUT, GRADING AND DRAINAGE.
10. (DETAIL NUMBER / SHEET NUMBER)
11. ALL BOLLARDS TO BE SEALED WITH 2 COATS EXTERIOR LATEX PAINT. COLOR TO BE 'AUTUMN GREEN' BY BENTAMIN-MOORE OR KELLY-MOORE. COLOR TO MATCH JACOB PARK BOLLARDS, WEST NINTH AND KINK, SANTA ROSA.



REVISIONS	BY
1-20-06	LP
9-11-06	LP
6-5-07	LP

WINFIELD SMITH ASSOCIATES ASLA
LANDSCAPE ARCHITECTS ■ SITE PLANNERS
13750 Arnold Drive, Glen Ellen, CA 95442
P.O. Box 388 ■ Glen Ellen, CA 95442
(707) 996-6677 ■ (707) 526-3922

APPROVED
CITY ENGINEER
BROYDON J. RIHA
BY _____
DATE 6-15-07

COFFEY PARK
SANTA ROSA, CALIFORNIA

SITE PLAN

REGISTERED LANDSCAPE ARCHITECT No. 1536 Signature 12/06 Date STATE OF CALIFORNIA

DATE	1-27-06
SCALE	1"=40'0"
DRAWN	LP
JOB	8495
SHEET	23
OF	29 SHEETS

DATAPRINT CORP 350 SO. CLAREMONT ST SAN MATEO, CA 94402
STOCKDRAFTING FORM NO. 101-54

CITY OF SANTA ROSA FILE No. 86-81